

ICOM

IC-200FX

245-247MHz CB 160 Channels

เล็กกระทัดรัด กำลังส่ง 500 มิลลิวัตต์ 160 ช่อง ไม่ต้องทำใบอนุญาต



หน้าจอ LCD ใหญ่ คมชัด
ขนาดเล็กน้ำหนักเบา 157 กรัม
ลำโพงมีความดังถึง 600 มิลลิวัตต์

VOX ฟังก์ชัน

CTCSS / DTCS โทน

ชาร์จผ่าน USB Type-C



ขนาดเท่าของจริง

กันน้ำ/กันฝุ่น IP54
ใช้งานต่อเนื่องยาวนาน 15 ชั่วโมง
ความทนทานระดับ MIL-STD 810G



SPECIFICATIONS

GENERAL	
Frequency coverage	245.0000-246.9875 MHz
Number of channels	160 channels
Type of emission	8K50F3E (12.5 kHz)
Antenna impedance	50 Ω
Power supply voltage	3.7 V DC
Current drain	Receive : 0.5 A Transmit : 0.8 A
Dimensions	H 156.0 × W 50.0 × D 26.7 mm , H 6.1 × W 2.0 × D 1.1 inch incl. antenna H 94.0 × W 50.0 × D 26.7 mm , H 3.7 × W 2.0 × D 1.1 inch excl. antenna
Weight	157 g, 5.5 oz, 177 g, 6.24 OZ (Including BP-304A battery pack and antenna)

TRANSMITTER	
Output power	500 mW
Max. fre. deviation	±2.5 kHz
Spurious emissions	70 dB
Adjacent channel power	65 dB
Audio harmonic distortion (At 1 kHz 40% Deviation)	5.0 %
FM Hum and Noise	40 dB
Ext. microphone connector	3-conductor 2.5 (d) mm (1/10") 8 Ω

RECEIVER	
Sensitivity	0.18μV (at 12 dB SINAD)
Audio power output	Internal Speaker : 600 mW @5 % distortion with 4 Ω External Speaker : 150 mW @5 % distortion with 8 Ω
Adjacent ch. selectivity	65 dB
Spurious response	70 dB
Intermodulation	70 dB
Hum and Noise	45 dB
Ext. microphone connector	3-conductor 2.5 (d) mm (1/10") 8 Ω

Applicable U.S. Military Specifications

Standard	MIL 810G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D -E and -F.

Ingress Protection Standard	
Dust & Water	IP54 (Dust-protection and water resistant)

All stated specifications are subject to change without notice or obligation.

Supplied Accessories * depending on version

- MB-127 Belt Clip • BP-304A Battery Pack • BC-262 Charging Cradle
- BC-263A USB Type-C™ AC adapter or USB Type-C™ Cable*

Made in Japan

The IC-200FX is designed by Icom Inc and produced at Wakayama Icom Inc.

OPTIONAL ACCESSORIES

OPC-2006LS

Conversion Cable for VOX function



OPC-2328

PTT Switch Cable



or

(Either the OPC-2006LS or OPC-2328 is required for use with the HS-94, HS-95 or HS-97.)

BATTERY PACK / BATTERY CHARGERS

BP-304A

Battery Pack
Li-ion 3.6 V
2350 mAh
2200 mAh min.



BC-263A

USB Type-C™
AC adapter



BC-262

Charging
Cradle



BC-264

Battery Charger



MICROPHONES

HM-153LS

Earphone
Microphone



HM-166LS

Earphone
Microphone



HM-183LS

Speaker
Microphone



HM-186LS

Speaker
Microphone



OTHER ACCESSORIES

MB-127

Belt clip



OPC-2006LS

Conversion Cable for VOX function



OPC-2328

PTT Switch Cable



HM-1LS-OW

Earphone Microphone
Acoustic Type Earphone



GSR-M2

Earphone Microphone
for Thai Version Only



Icom and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. USB Type-C is a trademark of USB Implementers Forum, Inc. QR Code is a trademark of DENSO WAVE INCORPORATED. All other trademarks are the properties of their respective holders.

Icom Inc.

1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icomjapan.com

Icom America Inc.
www.icomamerica.com

Icom (Europe) GmbH
www.icomeurope.com

Icom (Australia) Pty. Ltd.
www.icom.net.au

Icom Canada
www.icomcanada.com

Icom Spain S.L.
www.icomspain.com

Icom Asia Co., Ltd.
www.icomasia.com

Icom Brazil
E-mail: sales@icombrasil.com

Icom (UK) Ltd.
www.icomuk.co.uk

Shanghai Icom Ltd.
www.bjicom.com

Icom France s.a.s.
www.icom-france.com

Your local distributor/dealer:

บริษัท ซี.ซี.มอนเรดิโอ จำกัด
14/48-49 อาคารโครงการคาสเคด บางนา
หมู่ที่ 15 ตำบลบางแก้ว อำเภอบางพลี
จังหวัดสมุทรปราการ 10540
โทร. 02 090 2920-22 , 0816439181
แฟกซ์. 02 090 2922
Email : info@gsimon.com